

PLH 32

32 mm SDS-plus 3-mode L-shaped hammer

Features

- Tough, durable hammer with excellent drilling performance in concrete from the high torque motor and gears and a 3.8 joule single blow energy
- 900 watt motor combined with optimised drilling speed results in unsurpassed drilling performance
- Electronics with accelerator switch
- Good balance and easy handling from the compact L-shape design with AVS (Anti-Vibration-System) and soft grip handle
- Fast tool changing from the FIXTEC system with keyless chuck
- Heavy Duty magnesium gear casing for optimum seating of gears for a longer operational life
- Reliable safety clutch protects machine and user
- Roto-stop and variolock for maximum control when doing light chiselling work
- 4 m cable



RANGE SPEC (1)	PLH 32 XE
Sound pressure level (dB(A))	95
Sound pressure level uncertainty [dB[A]]	3
Sound power level [dB[A]]	106
Sound power level uncertainty [dB[A]]	3
Vibration chiselling uncertainty [mls ²]	1.5
Vibration drilling into concrete [mls ²]	25
Vibration drilling into concrete uncertainty [mls ²]	2.3
Supplied in	Kitbox
Vibration drilling (m/s ²)	22
Vibration chiseling (m/s<special id ="27" />)	20
Article Number	4933400071
Weight (kg)	3.6
Power input (W)	900
Max drilling steel (mm)	16
Max. drilling wood (mm)	40
Max. drilling masonry (mm)	32
Max. drilling concrete (mm)	32
Full load hammer action (bpm)	0 - 4500
Full load speed [rpm]	0 - 800
Blow energy [EPTA][J]	3.8